

LED Drivers

Constant Current

ILS Driver Part Number	Technical Parameters						ILS Products																
	Rating Watts	Output	IP Rating	Output Volts	PF	Dimming Type	Dragon 1/Oslon 1/SJ+K 1 PowerStar	Oslo4 PowerStars/Dragon4 Cluster	Oslo 9 + 10 Power Stars + Clusters	Oslo16 PowerClusters	Oslo17 Flood	Oslo27 /SJ27 PowerFlood	Duris P5/E5 PowerStar	Duris P5/E5 4 PowerStar/Eco One	Duris P5/E5 9 PowerStar	Long Linear Series	Anna 3	Anna 4	Anna 5	Anna 6	Anna 7	Petunia	
IZC015-005F-0067C-QA	5	150mA	IP67	20-33	0.6	NO							7-10	2	1								
IZC035-005F-0067C-QA	5	350mA	IP67	2-12	0.6	NO	1-3						2,4,6,8-P	2-P			1						
IZC070-005F-0067C-QA	5	700mA	IP67	2-5	0.6	NO	1-2																
IZC035-008F-5065C-SA	8	350 mA	IP65	3-36	0.5	no	1-6	1									1-2	1	1	1			
IZC070-008F-5065C-SA	8	700 mA	IP65	3-12	0.5	no	1-3										1						
IZC035-017F-0067A-SA	17	350 mA	IP67	6-48	0.6	no	3-12	1-3	1								1-4	1-3	1-2	1-2	1	1	
IZC035-018T-9500A-SA	18	350 mA dim	IP20	15-52	0.95	Triac	5-12	1-3									2-4	2-3	1-2	1-2	1	1	
IZC050-018T-9500A-SA	18	500 mA dim	IP20	9-36	0.95	Triac	3-9	1-2		1							1-3	1-2	1	1	1		
IZC070-018T-9500A-SA	18	700 mA dim	IP20	6-26	0.95	Triac	2-6	1									1-2	1	1	1			
IZC035-035F-9067C-QA	35	350mA	IP67	40-80	0.9	NO	13-26	3-6	2	1	1	1				480/786	5-8	4-6	3-5	3-4	2-3	2	
IZC070-035F-0067C-SA	35	700 mA	IP67	9 - 48	0.6	no	3-12	1-4	1								1-4	1-3	1-2	1-2	1	1	
IZC105-035F-9067C-QA	35	1050mA	IP67	16-32	0.9	NO	5-10	2	1								2-3	2	1-2	1	1		
IZC045-040A-9266C-SA	40	450 mA dim	IP66	30 -89	0.92	0-10 v	10-20	3-5			1					480	4-6	3-5	2-4	2-3	1-2	1	
IZC105-040A-0067C-QA	42	1050mA	IP67	24-40	0	0-10 v	8-13	2-3	1								3-4	2-3	2	2	1	1	
IZC070-050A-9267C-SA	50	700 mA dim	IP67	24 - 72	0.92	0-10 v	6-20	2-5	1-2		1					480	2-6	2-5	2-4	1-3	1-2	1	
IZC050-060F-9067C-QA	60	500 mA	IP67	40-110	0.9	no	15-30	4-7	2-3	1	1	1				All	5-10	2-8	3-6	3-5	3-4	2	
IZC105-060F-9067C-QA	60	1050mA	IP67	30-60	0.9	no	9-16	2-4	1	1	1					All	3-5	3-4	2-3	2	1-2	1	
IZC140-060F-9067C-QA	60	1400mA	IP67	20-42	0.9	no	7-14	2-3	1							480	3-4	2-3	2	2	1-2	1	
IZC070-075A-9267C-SA	75	700 mA dim	IP67	54 -108	0.92	0-10 v	20-30	5-7	2-3		1	1				All	6-10	5-7	4-6	4-5	3-4	2	

The number in the box indicates how many of each product can be driven from each driver.

LED Drivers

Constant Voltage

ILS Driver Part Number	Technical Parameters						ILS Products						
	Rating Watts	Output	IP Rating	Output Volts	PF	Dimming Type	Dragon3 Coins	Dragon 6/ Oslon 6 Strips	Dragon72/ Oslon72 PowerFlood	Duris E5 /PS 12 Tile	Duris E5 /PS 18 Strip	Duris E3 50 Tile	Duris E3 80 Strip
IZV012-010F-5065C-SA	10	12 volts	IP65	12 volts	0.5	no	1-2						
IZV024-018F-0067A-SA	18	24 volts	IP67	24 volts	0.6	no		1-2		1-3	1-2	1-6	1-2
IZV024-045F-9066C-SA	45	24 volts	IP66	24 volts	0.9	no		3-5		2-6	2-4	2-12	2-4
IZV024-060F-9067C-QA	60	24 volts	IP67	24 volts	0.9	no		6-9		16	4-8	4-24	4-8
IZV048-150F-9566C-SA	150	48 volts	IP66	48 Volts	0.95	no			1				

The number in the box indicates how many of each product can be driven from each driver.